



NT 65/2 Ap

The NT 65/2 Ap is a powerful, 2-motor wet and dry vac for professional applications. The suction power remains nearly constant due to the efficient cleaning of the flat pleated filter by blasts of air.

1 On-board storage

- The large on-board storage space on the casing head ensures that tools and accessories are always stored and close to hand.

2 Integrated drain hose (oil-resistant)

- Easily accessible drain hose for convenient liquid disposal.

3 ApClean (semi-automatic filter cleaning)

- The free filter means that the user can work for long intervals without interruption.
- Optimum suction power with high efficiency.

4 Hose and bend attachment

- Convenient suction hose and bend attachment for easy transport and storage.



NT 65/2 Ap

- Semi-automatic filter cleaning
- Flat pleated filter (dust class M)
- Drain hose and push handle

Technical data

Order no.	1.667-291.0	
EAN code	4039784727281	
Current type	Ph / V / Hz	1 / 220 - 240 / 50 - 60
Air flow	l/s	2 x 74
Vacuum	mbar / kPa	254 / 25.4
Container content	l	65
Container material	Plastic	
Rated input power	W	max. 2760
Standard nominal diameter	DN 40	
Cable length	m	10
Sound pressure level	dB(A)	73
Weight	kg	20
Dimensions (L x W x H)	mm	600 x 480 x 920

Equipment

Suction hose	m	4 / with bend	Protection class	II
Suction tube	piece(s) x m	2 x 0.5 / Metal	Stop swivel castor	■
Filter bag	piece(s)	1 / Paper		
Wet/dry floor nozzle	mm	360		
Crevice nozzle		■		
Drain hose (oil-resistant)		■		
Automatic cut-out features at max. filling quality		■		
Flat pleated filter		Paper		
Filter cleaning		ApClean (semi-automatic filter cleaning)		
Sturdy bumper		■		
Push handle		■		

■ Included in the scope of supply.

NT 65/2 AP

1.667-291.0

KÄRCHER


		Order no.	Quantity				Price	Description	
Flat pleated filter, paper									
Flat pleated filter, paper	1	6.904-283.0	1 piece(s)					Paper flat pleated filter (BIA-(U,S,G,C) dust class M) suitable for NT 65/2 Eco, NT 65/2 Eco Tc, NT 65/2 Eco Me.	■
Flat pleated filter HEPA, dust class H									
HEPA flat pleated filter	2	6.904-364.0	1 piece(s)					HEPA surface filter - dust class H (H 14) - with glass-fibre layers increases filter capacity when vacuuming health-endangering and carcinogenic dust.	□
Flat pleated filter, PES									
Flat pleated filter, PES	3	6.904-284.0	1 piece(s)					Flat filter (PES) - BIA-(U,S,G,C) dust class M: rotproof polyester fleece, ideal for wet use and abrasives. Standard for NT 72/2 Eco Tc.	□
Flat pleated filter, PTFE									
Flat pleated filter, PTFE	4	6.907-449.0	1 piece(s)					Polyester fleece with PTFE coating, dust class M, for Tact ² vacuum cleaners. Particularly suitable for very adhesive materials.	□
Wet filter bag									
Wet filter bag	5	6.904-252.0	5 piece(s)					Approved for dust class L, general cleaning, wet and dry, tear-resistant.	□
Paper filter bags									
Paper filter bags	6	6.904-285.0	5 piece(s)					5 3-ply, tear-resistant paper filter bags. BIA-(U, S, G, C) dust class M. For all NT 48/1, NT 65/2 Eco + Me and NT 72/2 Eco Tc models.	□
Plastic sacks for dust-free disposal									
Plastic bag for dust-free disposal	7	6.900-698.0	10 piece(s)					PE plastic sack.	□
Fabric filter									
Membrane filter	8	6.904-282.0	1 piece(s)					Polyester needle fleece membrane/fabric filter - BIA-C -, washable up to 40°C, metal fibres for earthing. Suitable for virtually all industrial two-motor NT vacuum cleaners.	□
Candle filter Wood	9	2.414-003.0	1 piece(s)					Wood cartridge filter made from textile material with PTFE coating and a brown label. For safely vacuuming large quantities of wood and fibre dust with the NT 65/2 and 75/2 twin-motor Tact vacuums.	□
Fleece filter bags									
Fleece filter bags	10	2.885-753.0	5 piece(s)					Large, tear-resistant, triple-layer fleece filter bags for all twin-motor wet and dry vacuum cleaners from Kärcher. Certified according to dust class M, suitable for container sizes from 65 to 75 litres.	□

■ Included in the scope of supply. □ Available accessories.

NT 65/2 AP

1.667-291.0

KÄRCHER


		Order no.	Quantity	ID	Length	Width	Price	Description	
Bend, plastic									
DN 40 bend	1	2.889-171.0	1 piece(s)	DN 40				Bend for the new clip system in nominal size DN 40.	■
Plastic bend	2	5.031-718.0	1 piece(s)	DN 35				Plastic bend (DN 35) with C-35 clip system. For all industrial single-motor NT 361 to NT 611 Eco models (except NT Eco M and NT Eco H).	□
Bend, plastic, electrically conductive	3	5.031-939.0	1 piece(s)	DN 35				Electrically conductive plastic bend (DN 35) with C-35 clip system. For all industrial single-motor NT 361 to NT 611 Eco models.	□
	4	5.032-427.0	1 piece(s)	DN 40				Electrically conductive plastic bend (DN 40) with C-40 clip system, suitable for all NT vacuum cleaners.	□
Bend	5	2.889-148.0	1 piece(s)	DN 35				Ergonomic bend for the new clip system. With airflow control slide, in an antistatic design.	□
Floor nozzles									
Wet/dry floor nozzle, plastic Adv, DN 40	6	2.889-153.0	1 piece(s)	40		360 mm		360 mm wide wet and dry floor nozzle with easy-to-change inserts, squeegees.	■
Wet and dry floor nozzle, aluminium, DN 40	7	6.903-018.0	1 piece(s)	40		370 mm		All-purpose aluminium nozzle with 370 mm working width. With height-adjustable side rollers, brush strips (6.903-064.0) and oil-resistant squeegees (6.903-081.0). Only for NT vacuum cleaners.	□
Multi-purpose nozzle, wet/dry	8	6.906-383.0	1 piece(s)	40		450 mm		All-purpose aluminium nozzle (DN 40) with 450 mm working width. With height-adjustable side rollers, brush strips (6.903-065.0) and oil-resistant squeegees (6.906-146.0). Only for NT vacuum cleaners.	□
	9	6.906-384.0	1 piece(s)	35		370 mm		All-purpose aluminium nozzle (DN 35) with 370 mm working width. With height-adjustable side rollers, brush strips (6.903-064.0) and oil-resistant squeegees (6.903-081.0). Only for NT vacuum cleaners.	□
Wet and dry floor nozzle	10	2.889-117.0	1 piece(s)	40		400 mm		The wet and dry floor nozzle (DN 40) allows quick changing of the squeegees/brush and is ideal for wet vacuum cleaning of large areas.	□
Crevice nozzles									
DN 40 crevice nozzle for wet and dry vacuum cleaner	11	5.130-655.0	1 piece(s)	DN 40				Plastic crevice nozzle in nominal width DN 40 for Kärcher wet and dry vacuum cleaners. Especially suitable for vacuuming out areas that are difficult to reach, such as joints, crevices and corners.	■
Crevice nozzle	12	6.900-385.0	1 piece(s)	DN 35	210 mm			Plastic crevice tool (DN 35) for vacuuming in crevices and corners. Length: 210 mm.	□
	13	6.900-922.0	1 piece(s)	35 mm	500 mm			Plastic crevice tool (DN 35) for vacuuming in crevices and corners. Length: 370 mm.	□
	14	6.905-817.0	1 piece(s)	40 mm	400 mm			Metal crevice tool (DN 40) for vacuuming in crevices and corners. Length: 400 mm.	□
Suction tubes, stainless steel									
Set suction tube stainless steel NW40 55	15	2.889-194.0	2 piece(s)	40	550 mm			Stainless steel suction tube set (2 × 0.55 m)	■
Suction tube	16	6.902-081.0	1 piece(s)	40	500 mm			Stainless steel suction tube (DN 40, 0.5 m) only suitable for NT vacuum cleaners.	□
	17	6.906-531.0	1 piece(s)	40	1000 mm			Stainless steel suction tube (DN 40, 1.0 m) only suitable for NT vacuum cleaners.	□
	18	6.902-154.0	1 piece(s)	35	500 mm			0.5 m long stainless steel suction tube (ID 35) for wet and dry vacuum cleaners. Ideal for frequent wet vacuuming applications and for vacuuming corrosive components.	□
Bends, stainless steel									
Bend, stainless steel, ID 35	19	6.903-141.0	1 piece(s)	DN 35				Stainless steel and crooked, ID 35	□

■ Included in the scope of supply. □ Available accessories.

NT 65/2 AP

1.667-291.0

KÄRCHER



		Order no.	Quantity	ID	Length	Width	Price	Description	
Bend, stainless steel, ID 40	20	6.902-079.0	1 piece(s)	DN 40				Stainless steel and crooked, ID 40	☐
Bends, metal									
Bend, metal	21	6.900-519.0	1 piece(s)	DN 35				Robust, chromium-plated metal bend (DN 35), can be used instead of a plastic bend (with clip system adapter 5.407-112.0, C 35-DN 35, plastic, el.).	☐
	22	6.900-276.0	1 piece(s)	DN 40				Robust, chromium-plated metal bend (DN 40), can be used instead of a plastic bend (with clip system adapter 5.407-111.0, C 40-DN 40, plastic, el.).	☐
All-purpose brushes									
All-purpose brush	23	6.903-863.0	1 piece(s)	35 mm	120 mm			Natural bristles (ox hair), bristle element 120 x 45 mm.	☐
Car cleaning nozzles									
DN 40 car nozzle	24	6.900-952.0	1 piece(s)	DN 40		90 mm		For retrofitting older Kärcher wet and dry vacuum cleaner models with bends in DN 40: Flat angled, convenient, plastic car cleaning nozzle with a working width of approx. 90 mm.	☐
Rubber suction tools, nose 45°									
Rubber suction tool, nose 45°	25	6.902-104.0	1 piece(s)	35 mm	220 mm			45° rubber suction nozzle (DN 35), oil-resistant and suitable for vacuuming machines. Only for NT vacuum cleaners.	☐
	26	6.902-105.0	1 piece(s)	40 mm	220 mm			45° rubber suction nozzle (DN 40), oil-resistant and suitable for vacuuming machines. Only for NT vacuum cleaners.	☐
Pipe dusting nozzles									
Pipe brush 35/100	27	6.903-035.0	1 piece(s)	35 mm				Plastic, pipe diameter 100 mm	☐
Pipe brush 35/200	28	6.903-036.0	1 piece(s)	35 mm				Plastic, pipe diameter 200 mm	☐
Suction tubes, metal									
Suction tube	29	6.900-514.0	1 piece(s)	35	500 mm			Chromium-plated metal suction tube (DN 35, 1x0.5 m), standard for virtually all single-motor industrial NT vacuum cleaners.	☐

■ Included in the scope of supply. □ Available accessories.

NT 65/2 AP 1.667-291.0


KÄRCHER


		Order no.	Quantity	ID	Length	Price	Description	
Complete suction hoses (clip system)								
Suction hose DN 40, length 4 m	1	2.889-138.0	1 piece(s)	DN 40	4 m		4 m long suction hose with new bayonet and clip fastener.	■
Suction hose	2	4.440-678.0	1 piece(s)	DN 40	4 m		With bend, C ID 40.	□
Suction hose + PFC module	3	4.440-679.0	1 piece(s)	DN 40	4 m		With bend and module (4.060-474.0).	□
Suction hose + PFC module, electrically conductive	4	4.440-728.0	1 piece(s)	DN 40	4 m		With bend and module (4.060-533.0), electrically conductive.	□
Electrically conductive suction hose	5	2.889-137.0	1 piece(s)	DN 35	4 m		4 m suction hose with new bayonet and clip fastener. Electrically conductive.	□
Suction hose	6	2.889-139.0	1 piece(s)	DN 40	2.5 m		Suction hose with new bayonet and clip fastener. Length: 2.5 m.	□
Suction hose, oil-resistant	7	2.889-140.0	1 piece(s)	DN 40	4 m		Oil-resistant suction hose with new bayonet and clip fastener. Length: 4 m.	□
Electrically conductive suction hose	8	2.889-141.0	1 piece(s)	DN 40	4 m		4 m long, electrically conductive suction hose with new bayonet and clip fastener.	□
	9	2.889-142.0	1 piece(s)	DN 40	2.5 m		Suction hose, electrically conductive, with new bayonet and clip fastener. 2.5 m long.	□
Repair kits								
Repair kit, C 40	10	2.639-873.0	1 piece(s)	C- 40			Suction hose repair kit (clip system).	□
Repair kit, ID 61	11	2.862-038.0	1 piece(s)	DN 61			Suction hose repair kit.	□
Repair kit ID 40	12	2.889-150.0	1 piece(s)	DN 40			Repair kit ID 40 for the new clip system.	□
Suction hoses (clip system)								
Suction hose	13	6.906-279.0	1 piece(s)	DN 40	10 m		With bayonet and clip connection, C-45.	□
	14	6.906-321.0	1 piece(s)	40	4 m		With bayonet and clip connection, C 40.	□
	15	6.906-714.0	1 piece(s)	DN 40	4 m		With bayonet and clip connection, oil-resistant, C-45.	□
	16	6.906-635.0	1 piece(s)	DN 40	16 m		With bayonet and clip connection, C-40.	□
	17	6.906-877.0	1 piece(s)	DN 40	10 m		With bayonet and clip connection, electrically conductive, C-40.	□
Suction hoses complete								
Suction hose, complete	18	4.440-264.0	1 piece(s)	DN 61	4 m		Plastic.	□
	19	4.440-328.0	1 piece(s)	DN 61	3 m		Industrial hose, PVC / elastomer with steel spiral, smooth inside.	□
	20	4.440-467.0	1 piece(s)	DN 61	10 m		Plastic.	□
Suction hose, complete, oil-resistant	21	4.440-613.0	1 piece(s)	DN 61	4 m		Oil-resistant.	□
Suction hose, complete, electrically conductive	22	4.440-616.0	1 piece(s)	DN 61	4 m		Electrically conductive.	□
Suction hose, complete	23	4.440-263.0	1 piece(s)	DN 40	4 m		Plastic.	□
	24	4.440-303.0	1 piece(s)	DN 40	4 m		Oil-resistant.	□
	25	4.440-463.0	1 piece(s)	DN 40	10 m		Plastic.	□
	26	4.440-466.0	1 piece(s)	DN 40	10 m		Electrically conductive, plastic.	□
Suction hose, complete, oil-resistant	27	4.440-612.0	1 piece(s)	DN 40	10 m		Oil-resistant.	□
Hose connection								
Adapter, ID 32/35, with internal thread	28	6.902-077.0	1 piece(s)	DN 32			For connecting two suction hoses (not ESB 28 and 34).	□
Connecting adapter, ID 40, with internal thread	29	6.900-286.0	1 piece(s)	DN 40			For connecting two suction hoses, threaded at both ends.	□
Extension hoses (clip system)								
Extension hose	30	6.906-344.0	1 piece(s)	DN 40	2.5 m		For all C-40 hoses.	□
	31	2.889-146.0	1 piece(s)	DN 40	2.5 m		Extension hose for new clip system ID 40. Length: 2.5 m.	□

■ Included in the scope of supply. □ Available accessories.

NT 65/2 AP

1.667-291.0



		Order no.	Flow rate	Inlet temperature	Length	Length	Price	Description	
Teleskopstangen									
Telescopic lance TL 10 H	1	4.762-611.0		max. 60 °C				Up to 10 m reach: hybrid telescopic lance TL 10 H. Comprising carbon-glass fibre mix and suitable for multifunctional use. Simple retraction and extension thanks to quick-release fasteners.	☐
Telescopic lance TL 10 C	2	4.762-612.0		max. 60 °C				Carbon fibre telescopic lance TL 10 C. With up to 10 m reach and practical quick-release fasteners. Multifunctional use for cleaning facades, windows or solar panels.	☐
TL vacuum cleaner adapter	3	9.751-306.0						TL suction cup for 10 and 14 m long telescopic lances comprising suction bend connection (DN 35, DN 40) and connection for the suction nozzles.	☐

■ Included in the scope of supply.
 ☐ Available accessories.

NT 65/2 AP 1.667-291.0

KÄRCHER



		Order no.	Quantity	ID				Price	Description	
Y-adapter kit										
Y-adapter kit	1	2.637-217.0	1 piece(s)	35 mm					Plastic distributor - suitable for NT vacuum cleaners.	☐
Connection adapter C ID (clip to cone), electrically conductive										
Connection adapter C DN 35	2	5.407-112.0	1 piece(s)	35 mm					C 35 hose connector for DN 35 accessory, electrically conductive.	☐
Connection adapter C DN 40	3	5.407-109.0	1 piece(s)	C-DN 40					Electrically conductive adapter (C 40) with DN 35 connection for connecting DN 35 accessories to an industrial C 40 or C-DN 40 suction hose. Suitable for NT vacuum cleaners.	☐
	4	5.407-111.0	1 piece(s)	40 mm					C 40 hose connector for DN 40 accessory, electrically conductive.	☐
Adapter clip DN 35 on cone DN 35	5	5.407-005.0							Adapter clip system DN 35 for connecting suction tubes and small nozzles to cone DN 35. Perfect for vehicle interior cleaning, even without the connection of other nozzles.	☐
Adapter clip DN 40 to cone DN 40	6	5.407-006.0		DN 40					For connecting small nozzles and suction tubes with cone DN 40: Adapter clip system DN 40. Ideal for vehicle interior cleaning tasks, with no need to connect additional nozzles.	☐
Connection adapter for power tools, clip-on, electrically conductive										
Connection adapter for power tools, C 35, electrically conductive	7	5.453-042.0	1 piece(s)	35 mm					3-way plastic adapter. For DN 26 to DN 36. For connecting power tools to an industrial C or C-DN 35 suction hose. Suitable for NT vacuum cleaners.	☐
	8	5.453-048.0	1 piece(s)	35 mm					Inside Ø 25.4 mm, outside Ø 34.6 mm/ 38 mm, electrically conductive. Only NT vacuums.	☐
	9	5.453-050.0	1 piece(s)	35 mm					Inside Ø 27 mm, outside Ø 36.5 mm/38.8 mm, electrically conductive. Only NT vacuums.	☐
Adapter for electric power tools, screwable										
Adapter for electric power tools, screwable, ID 35	10	5.453-016.0	1 piece(s)	35 mm					3-way plastic adapter with fitting instructions. For DN 26 to DN 36. For connecting to an industrial DN 35 suction hose.	☐
	11	5.453-026.0	1 piece(s)	35 mm					Inside Ø 28.6 mm, outside Ø 37.3/38.8 mm.	☐
	12	6.902-059.0	1 piece(s)	35 mm					Electrically conductive power tool adapter, threaded. Internal diameter: 32 mm.External diameter: 39 mm.	☐
	13	6.902-095.0	1 piece(s)	35 mm					2-way power tool adapter, threaded. For connecting to an industrial DN 35 suction hose. Internal diameter: 28 mm. External diameter: 34 mm and 38.8 mmSuitable for NT vacuum cleaners.	☐
Expansion pieces (tube -> nozzle)										
Adapter	14	5.453-019.0	1 piece(s)	40 mm					From DN 40 to DN 61: Plastic adapter (electrically non-conductive). Suitable for NT vacuum cleaners.	☐
Reducing sleeves										
Reducer	15	5.407-108.0	1 piece(s)	40 mm					Threaded reducer - from C-40 to DN 35. Suitable for NT vacuum cleaners.	☐
NT reduction bushing with clip system for DN 40 suction hoses on accessory DN 35	16	5.407-113.0	1 piece(s)	40 mm					Reducer (C 40 to C 35) for connecting accessories with C-35 clip connection to suction hoses with C 40 clip system.	☐
Reducers (tube -> nozzle)										
Reducer	17	6.902-017.0	1 piece(s)	40 mm					Reducer for accessory extension. Ideal for accessories with DN 35 connecting cone in combination with accessories with DN 40 connecting cone.	☐
Reducer from ID 35 to ID 32	18	6.902-072.0	1 piece(s)	35 mm					Reducer with internal connecting cone DN 32. Ideal for accessories from the industrial vacuum cleaner range in combination with industrial NT vacuum cleaners.	☐
Reduction/expansion adapter kit										
Set of reducers / adapter sleeves	19	2.860-117.0	1 piece(s)						DN 40/35, DN 35/32 (tube -> nozzle), plastic.	☐

■ Included in the scope of supply. □ Available accessories.

NT 65/2 AP
1.667-291.0



		Order no.	ID				Price	Description	
Target-group-specific accessory kits for vacuum cleaners									
Professional cleaning kit NT DN 40	1	2.637-353.0	DN 40					Professional wet and dry accessory kit in nominal size DN 40 for Kärcher vacuum cleaners. The wet and dry professional cleaning kit comprises a suction hose, bend, two suction tubes, crevice nozzle and floor nozzle.	☐
Car cleaning accessory kit	2	2.862-166.0	DN 35					Vehicle interior cleaning accessory kit in nominal width DN 35 for Kärcher wet and dry vacuum cleaners. The kit comprises various nozzles and adapter pieces in nominal widths DN 35 and DN 40.	☐
Swarf kit	3	2.640-760.0	DN 61					Wet and dry accessory kit in nominal size DN 61 for vacuuming chips with Kärcher vacuum cleaners. The chip kit comprises an oil-resistant suction hose, a crevice nozzle and a rubber suction nozzle.	☐

■ Included in the scope of supply. □ Available accessories.

NT 65/2 AP
1.667-291.0



		Order no.	Quantity	Width			Price	Description	
Other accessories NT									
CS 40 Me	1	2.863-026.0	1 piece(s)					The highly efficient CS 40 Me cyclone preseparator for all Kärcher wet and dry vacuum cleaners is a specially designed accessory for fine dust applications on construction sites or in industry.	☐
Adapter connection, electroconductive	2	5.031-436.0						Electroconductive, universal adapter for connecting old NT hoses of nominal widths DN 35, 40, 50 to the new accessory system for wet and dry vacuum cleaners from Kärcher.	☐

■ Included in the scope of supply. ☐ Available accessories.

NT 65/2 AP
1.667-291.0



		Order no.	Quantity	ID	Length	Width	Price	Description	
Modification kit, non-conductive media									
Attachment kit, non-conductive media Tact ² + Ap	1	2.642-602.0	1 piece(s)					For switching off when vacuuming non-conductive fluids such as oils and greases	☐

■ Included in the scope of supply. ☐ Available accessories.

NT 65/2 AP
1.667-291.0



		Order no.	Length	Colour	Quantity	Price	Description	
Miscellaneous								
Extension cable	1	6.647-022.0	20 m		1 piece(s)		Extension cable, 20 m, 3x1.5 mm ² . With splash-proof earthing pin plug, strain relief and anti-kink sleeve.	☐

■ Included in the scope of supply. ☐ Available accessories.