





## HD 6/15-4 Classic

Single-phase, compact, strong: the service-friendly HD 6/15-4 Classic high-pressure cleaner with a 600 l/h water flow, powerful crankshaft pump, ceramic piston and the latest sealing technology.



### 1 Durable and robust

- Extra large crankshafts and connecting rods with robust ball bearings.
- Ceramic pistons for reduced wear and tear.

### 2 Especially easy to maintain

- Wide-opening machine cover for easy access to all service and maintenance-relevant components.
- Large water fine filter for protecting the pump.

### 3 Improved cleaning performance

- Patented Kärcher power flat jet nozzles: up to 40 percent more impact force than conventional nozzles.
- High area coverage and thorough dirt removal.

### 4 Excellent mobility

- Large wheels and ergonomic push handle ensure optimal turning manoeuvrability and easy handling.
- The foldable push handle enables space-saving storage.



## HD 6/15-4 Classic

- Durable crankshaft pump with ceramic-coated pistons
- Large, transparent water filter
- Infinitely variable pressure regulation

### Technical data

|                        |               |                  |
|------------------------|---------------|------------------|
| Order no.              | 1.367-306.0   |                  |
| EAN code               | 4039784858756 |                  |
| Current type           | Ph / V / Hz   | 1 / 220-240 / 50 |
| Flow rate              | l/h           | 450-600          |
| Working pressure       | bar / MPa     | 70-150 / 7-15    |
| Max. pressure          | bar           | 190              |
| Max. inlet temperature | °C            | 60               |
| Connection load        | kW            | 3.4              |
| Weight                 | kg            | 52               |
| Dimensions (L × W × H) | mm            | 709 × 469 × 1000 |

### Equipment

|                                      |    |                    |
|--------------------------------------|----|--------------------|
| Spray gun                            |    | standard           |
| High-pressure hose                   | m  | 10 / DN 6, 250 bar |
| Spray lance                          | mm | 850                |
| Power nozzle                         |    | ■                  |
| ANTI!Twist                           |    | -                  |
| Pressure cut-off                     |    | ■                  |
| Servo Control                        |    | -                  |
| Crankshaft pump with ceramic pistons |    | ■                  |
| ■ Included in the scope of supply.   |    |                    |

# HD 6/15-4 CLASSIC

## 1.367-306.0

**KÄRCHER**




|                                                                        |    | Order no.   | ID   | Max. working pressure | Length | Price | Description                                                                                                                                                                 |   |
|------------------------------------------------------------------------|----|-------------|------|-----------------------|--------|-------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---|
| <b>Standard with unions on both sides</b>                              |    |             |      |                       |        |       |                                                                                                                                                                             |   |
| High-pressure hose, 30 m, ID 8, incl. rotary coupling                  | 1  | 6.390-293.0 | ID 8 | 315 bar               | 30 m   |       | To extend the operating radius with the high-pressure cleaner. Connection on both sides M22 x 1.5.                                                                          | ▲ |
| High-pressure hose, 15 m, ID 8, 315 bar, including rotary coupling     | 2  | 6.390-010.0 | ID 8 | 315 bar               | 15 m   |       | With screw connections on both sides, M 22 x 1.5 with bend protection.                                                                                                      | ▲ |
| High-pressure hose, 20 m, ID 8, 315 bar, extension piece               | 3  | 6.390-031.0 | ID 8 | 315 bar               | 20 m   |       | Screw connections at both ends, M 22 x 1.5, with kink protection.                                                                                                           | ▲ |
| High-pressure hose, 10 m, ID 8, 315 bar, extension                     | 4  | 6.391-342.0 | ID 8 | 315 bar               | 10 m   |       | To extend the operating radius with the high-pressure cleaner. Connection on both sides M22 x 1.5.                                                                          | □ |
| <b>Longlife 400 with unions on both sides</b>                          |    |             |      |                       |        |       |                                                                                                                                                                             |   |
| High-pressure hose Longlife 400, 15 m, ID 8, including rotary coupling | 5  | 6.389-709.0 | ID 8 | 400 bar               | 15 m   |       | With rotary coupling, 2 x M 22 x 1.5                                                                                                                                        | ▲ |
| High-pressure hose Longlife 400, 20 m, ID 8, extension                 | 6  | 6.390-027.0 | ID 8 | 400 bar               | 20 m   |       | with rotary coupling, 2 x M 22 x 1.5                                                                                                                                        | ▲ |
| High-pressure hose Longlife 400, 30 m, ID 8, including rotary coupling | 7  | 6.390-294.0 | ID 8 | 400 bar               | 30 m   |       | With rotary coupling, 2 x M 22 x 1.5                                                                                                                                        | ▲ |
| High-pressure hose Longlife 400, ID 8, 400 bar, 1.5 m                  | 8  | 6.392-282.0 | ID 8 | 400 bar               | 1.5 m  |       | Screw connections at both ends, M 22 x 1.5, with kink protection. Dual layer steel wire reinforced.                                                                         | □ |
| High-pressure hose 1.5 m, ID 8, including connectors                   | 9  | 6.390-178.0 | ID 8 | 400 bar               | 1.5 m  |       | 1.5 m high-pressure hose (DN 8, M 22 x 1.5) with kink protection and connectors at both ends. For connecting to hose reels with appropriate connector (M 22 x 1.5).         | □ |
| High-pressure hose Longlife 400, 10 m, ID 8, including rotary coupling | 10 | 6.388-083.0 | ID 8 | 400 bar               | 10 m   |       | 10 m high-pressure hose Longlife 400 (DN 8) with rotary coupling, two layer high-strength steel wire reinforced. Connectors at both ends. M 22 x 1.5, with kink protection. | □ |

■ Included in the scope of supply. □ Available accessories. ▲ Extension hose.

# HD 6/15-4 CLASSIC

## 1.367-306.0

**KÄRCHER**



|                                            |   | Order no.   | Flow rate |  |  |  | Price | Description                                                                                                                                                                                     |   |
|--------------------------------------------|---|-------------|-----------|--|--|--|-------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---|
| <b>Trigger guns</b>                        |   |             |           |  |  |  |       |                                                                                                                                                                                                 |   |
| Standard trigger gun                       | 1 | 9.751-139.0 |           |  |  |  |       | High-pressure gun for machines of the HD Classic range. With adapter for high-pressure hoses M 22 x 1.5.                                                                                        | ■ |
| EASY!Force Advanced                        | 2 | 4.118-005.0 |           |  |  |  |       | Effortless, not energy-sapping: the EASY!Force high-pressure gun uses the recoil force of the high-pressure jet to reduce the holding force for the operator to zero.                           | □ |
| EASY!Force conversion kit 2 - from machine | 3 | 4.111-051.0 |           |  |  |  |       | Developed for retrofitting existing high-pressure cleaners from Kärcher: EASY!Force conversion kit 2 with EASY!Force high-pressure gun, spray lance, high-pressure hose and necessary adapters. | □ |
| <b>Quick connect</b>                       |   |             |           |  |  |  |       |                                                                                                                                                                                                 |   |
| Quick coupling                             | 4 | 6.401-458.0 |           |  |  |  |       | For fast changes between different spray lances/accessories. Perfect for Kärcher spray unit, suitable for trigger gun/spray lance interface. With M 22 x 1.5 internal thread.                   | □ |
| Male coupling                              | 5 | 6.401-459.0 |           |  |  |  |       | Hardened stainless steel male coupling for quick coupling 6.401-458. With M 22 x 1.5 external thread.                                                                                           | □ |

■ Included in the scope of supply. □ Available accessories. ▲ Extension hose.

# HD 6/15-4 CLASSIC

## 1.367-306.0

**KÄRCHER**


|                                          |    | Order no.   | Max. working pressure | Length  |  |  | Price | Description                                                                                                                                                                                                                                 |   |
|------------------------------------------|----|-------------|-----------------------|---------|--|--|-------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---|
| <b>Spray lance</b>                       |    |             |                       |         |  |  |       |                                                                                                                                                                                                                                             |   |
| Spray lance 850mm                        | 1  | 9.751-044.0 |                       |         |  |  |       | 600mm zinc-coated spray lance with hand screw connection is suitable for machines of the HD Classic range. Spray lance is non-rotatable.                                                                                                    | ■ |
| 250 mm lance, non-rotatable              | 2  | 4.760-667.0 |                       | 250 mm  |  |  |       | 250 mm stainless steel lance. With manual coupling. Non-rotatable.                                                                                                                                                                          | □ |
| 550 mm lance, non-rotatable              | 3  | 4.760-665.0 |                       | 550 mm  |  |  |       | 550 mm stainless steel lance. With manual coupling. Non-rotatable.                                                                                                                                                                          | □ |
| 600 mm spray lance                       | 4  | 9.751-140.0 |                       |         |  |  |       | 600 mm long, zinc coated spray lance with hand screw connection. Not rotatable.                                                                                                                                                             | □ |
| <b>Rotating spray lances</b>             |    |             |                       |         |  |  |       |                                                                                                                                                                                                                                             |   |
| 600 mm spray pipe, rotatable             | 5  | 4.760-664.0 | 300 bar               | 600 mm  |  |  |       | 600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.                                                                                                         | □ |
| Spray lance, 840 mm, rotatable           | 6  | 4.760-663.0 | 300 bar               | 840 mm  |  |  |       | 850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.                                                                                                         | □ |
| 1050 mm spray pipe, rotatable            | 7  | 4.760-660.0 | 300 bar               | 1050 mm |  |  |       | 1050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.                                                                                                        | □ |
| 1550 mm spray pipe, rotatable            | 8  | 4.760-661.0 | 300 bar               | 1550 mm |  |  |       | 1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.                                                                                                        | □ |
| 2050 mm spray pipe, rotatable            | 9  | 4.760-662.0 | 300 bar               | 2050 mm |  |  |       | 2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.                                                                                                        | □ |
| <b>Angular spray lance</b>               |    |             |                       |         |  |  |       |                                                                                                                                                                                                                                             |   |
| Spray lance for toilets and rain gutters | 10 | 4.760-073.0 |                       |         |  |  |       | Stainless steel lance WC and gutter with nozzle insert. Specially shaped for effective and hygienic cleaning of gutters and toilets.                                                                                                        | □ |
| <b>Flexible spray lance</b>              |    |             |                       |         |  |  |       |                                                                                                                                                                                                                                             |   |
| Flexible lance 1050 mm                   | 11 | 6.394-654.0 | 210 bar               | 1050 mm |  |  |       | 1050 mm flexible lance with variable bend from 20° to 140°, ideal for cleaning difficult to reach areas, e.g. gutters.                                                                                                                      | □ |
| High-pressure M18x1.5 articulated joint  | 12 | 4.481-039.0 | 300 bar               |         |  |  |       | High-pressure articulated joint: Thanks to infinite angle adjustment up to 120°, this tool is ideal to effortlessly clean hard-to-reach areas. Simply attach to the spray lance of the pressure washer.                                     | □ |
| <b>Telescopic spray lance</b>            |    |             |                       |         |  |  |       |                                                                                                                                                                                                                                             |   |
| Telescopic spray lance                   | 13 | 6.394-690.0 | 225 bar               | 5400 mm |  |  |       | Can be continuously extended from 1.8 to 5.4 m. For cleaning areas that are difficult to reach, such as ceilings or facades. With integrated HD trigger gun, M 22 x 1.5 connection with rotary coupling. Connection for M 18 x 1.5 nozzles. | □ |
| Strap for telescopic spray pipe          | 14 | 6.373-987.0 |                       |         |  |  |       | Convenient strap for relief when working with the telescopic spray lance (6.394-690). The burden is optimally distributed on the body and longer periods of use are possible.                                                               | □ |
| <b>Gutter cleaner</b>                    |    |             |                       |         |  |  |       |                                                                                                                                                                                                                                             |   |
| Gutter cleaning lance                    | 15 | 2.642-305.0 |                       |         |  |  |       | The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates.                                                                   | □ |
| <b>Undercarriage spray lance</b>         |    |             |                       |         |  |  |       |                                                                                                                                                                                                                                             |   |
| Underbody lance                          | 16 | 4.760-245.0 |                       | 700 mm  |  |  |       | Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle.                                                                                                                               | □ |

■ Included in the scope of supply. □ Available accessories. ▲ Extension hose.

# HD 6/15-4 CLASSIC

## 1.367-306.0



|                                     |   | Order no.   | Nozzle size |  |  |  | Price | Description                                                                                          |   |
|-------------------------------------|---|-------------|-------------|--|--|--|-------|------------------------------------------------------------------------------------------------------|---|
| <b>Power nozzle spray angle 25°</b> |   |             |             |  |  |  |       |                                                                                                      |   |
| Power nozzle 25° - 036              | 1 | 2.883-821.0 | 36          |  |  |  |       | Fan jet nozzle with 25° spray angle, suitable for large areas and removing stubborn dirt and stains. | ■ |
| <b>HP nozzle spray angle 0°</b>     |   |             |             |  |  |  |       |                                                                                                      |   |
| High-pressure nozzle 0° - 040       | 2 | 2.884-533.0 | 40          |  |  |  |       | High-pressure nozzle with powerful jet for extremely stubborn dirt.                                  | □ |
| <b>Power nozzle spray angle 15°</b> |   |             |             |  |  |  |       |                                                                                                      |   |
| Power nozzle 15° - 036              | 3 | 2.885-225.0 | 36          |  |  |  |       | Flat stream for stubborn contaminations.                                                             | □ |
| <b>Power nozzle spray angle 40°</b> |   |             |             |  |  |  |       |                                                                                                      |   |
| Power nozzle 40° - 040              | 4 | 2.884-522.0 | 40          |  |  |  |       | Power nozzle with a 40° spray angle and fan jet, suitable for large areas and sensitive surfaces.    | □ |

■ Included in the scope of supply. □ Available accessories. ▲ Extension hose.

# HD 6/15-4 CLASSIC

## 1.367-306.0



|                                 |   | Order no.   | Max. working pressure | Nozzle size |  |  | Price | Description                                                                                                                                                                                                        |                          |
|---------------------------------|---|-------------|-----------------------|-------------|--|--|-------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|
| <b>Dirt Blaster, small</b>      |   |             |                       |             |  |  |       |                                                                                                                                                                                                                    |                          |
| Dirt blaster - more Performance | 1 | 4.767-231.0 | 180 bar               | 40          |  |  |       | With rotating point jet for more efficient removal: the new performance dirt blaster with nozzle size 040 achieves up to 50% higher cleaning and area performance than its predecessor.                            | <input type="checkbox"/> |
| <b>Dirt blaster, large</b>      |   |             |                       |             |  |  |       |                                                                                                                                                                                                                    |                          |
| Dirt blaster                    | 2 | 4.763-252.0 | 300 bar               | 40          |  |  |       | The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C.                          | <input type="checkbox"/> |
| <b>Triple nozzles</b>           |   |             |                       |             |  |  |       |                                                                                                                                                                                                                    |                          |
| Triple nozzle 036               | 3 | 4.767-148.0 | 300 bar               | 36          |  |  |       | Triple nozzle with manual nozzle changeover. Convenient spray adjustment. For machines with an injector, the low-pressure flat stream is useful for cleaning agent suction and application. Connection M 18 x 1.5. | <input type="checkbox"/> |

■ Included in the scope of supply. □ Available accessories. ▲ Extension hose.

# HD 6/15-4 CLASSIC

## 1.367-306.0

**KÄRCHER**



|                                              |    | Order no.   | Max. working pressure | Nozzle size | Diameter | Price | Description                                                                                                                                                                   |                          |
|----------------------------------------------|----|-------------|-----------------------|-------------|----------|-------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|
| <b>Pipe cleaning hose, ID 6</b>              |    |             |                       |             |          |       |                                                                                                                                                                               |                          |
| Pipe cleaning hose, ID 6, 10 m, max. 250 bar | 1  | 6.110-046.0 | 250 bar               |             |          |       | The 10 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).                                        | <input type="checkbox"/> |
| Pipe cleaning hose, DN 6, 20 m, max. 120 bar | 2  | 6.390-028.0 | 120 bar               |             |          |       | The 20 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).                                        | <input type="checkbox"/> |
| Pipe cleaning hose, ID 6, 20 m, max. 250 bar | 3  | 6.110-008.0 | 250 bar               |             |          |       |                                                                                                                                                                               | <input type="checkbox"/> |
| Pipe cleaning hose, DN 6, 30 m, max. 120 bar | 4  | 6.390-029.0 | 120 bar               |             |          |       | 30 m flexible high-pressure hose (DN 6) for cleaning pipes (threaded connection for R 1/8 nozzle).                                                                            | <input type="checkbox"/> |
| Pipe cleaning hose, ID 6, 30 m, max. 250 bar | 5  | 6.110-047.0 | 250 bar               |             |          |       | The 30 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).                                        | <input type="checkbox"/> |
| Pipe cleaning hose, DN 6, 20 m, max. 250 bar | 6  | 6.390-030.0 | 250 bar               |             |          |       | The 20 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).                                        | <input type="checkbox"/> |
| <b>Pipe cleaning nozzle</b>                  |    |             |                       |             |          |       |                                                                                                                                                                               |                          |
| Pipe cleaning dirt blaster D21/040           | 7  | 4.765-001.0 |                       | 40          | 21 mm    |       | The forward-tilted rotating pencil jet removes the most stubborn dirt. The three backwards-tilted jets ensure the necessary forward movement, as well as convenient handling. | <input type="checkbox"/> |
| Pipe cleaning dirt blaster D30/040           | 8  | 4.765-004.0 |                       | 40          | 30 mm    |       |                                                                                                                                                                               | <input type="checkbox"/> |
| Pipe cleaning nozzle                         | 9  | 5.763-015.0 |                       | 55          | 16 mm    |       | 16 mm pipe cleaning nozzle with internal thread. Various jet directions for environmentally-friendly cleaning of blocked drains and pipes.                                    | <input type="checkbox"/> |
|                                              | 10 | 5.763-016.0 |                       | 60          | 16 mm    |       |                                                                                                                                                                               | <input type="checkbox"/> |
|                                              | 11 | 5.763-017.0 |                       | 50          | 30 mm    |       | Pipe cleaning nozzle with inner thread. Different spray directions. The hose moves freely through the pipe. (R 1/8" connection, 3 x 30° backwards, diameter 30 mm.)           | <input type="checkbox"/> |
| Rotating pipe cleaning nozzle                | 12 | 6.415-428.0 |                       | 50          | 16 mm    |       | Pipe cleaning nozzle with four rotating jets and inner thread. Different spray directions. The hose moves freely through the pipe. With R 1/8" connection.                    | <input type="checkbox"/> |

■ Included in the scope of supply. □ Available accessories. ▲ Extension hose.

# HD 6/15-4 CLASSIC

## 1.367-306.0

**KÄRCHER**



|                                                    |    | Order no.   | Flow rate   | Nozzle size | Diameter | Price | Description                                                                                                                                                                                                                                                                                                                                                                                                             |                          |
|----------------------------------------------------|----|-------------|-------------|-------------|----------|-------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|
| <b>FR Classic surface cleaner</b>                  |    |             |             |             |          |       |                                                                                                                                                                                                                                                                                                                                                                                                                         |                          |
| FR Classic surface cleaner                         | 1  | 2.643-476.0 |             |             |          |       | The ideal entry-level model in the Kärcher surface cleaner range for cleaning surfaces indoors and outdoors. With splash guard and up to 150 bar working pressure.                                                                                                                                                                                                                                                      | <input type="checkbox"/> |
| <b>Hard Surface Cleaner FRV 30</b>                 |    |             |             |             |          |       |                                                                                                                                                                                                                                                                                                                                                                                                                         |                          |
| FRV 30 surface cleaner                             | 2  | 2.642-999.0 |             |             |          |       | With the integrated and automatic suction of the dirty water, the FRV 30 makes surface cleaning even more efficient. There is no longer a need to rinse the surface after cleaning, as the dirty water can be removed through the 5m suction hose, which is supplied. Additional features include the non-marking steering rollers and double ceramic bearings. Machine specific nozzle kit must be ordered separately. | <input type="checkbox"/> |
| Rubber lip for FRV 30                              | 3  | 2.642-910.0 |             |             |          |       | For smooth floors indoors. The squeegee increases the suction performance of the FRV 30 and minimises the amount of water remaining. This means the floor is dry in just a few minutes.                                                                                                                                                                                                                                 | <input type="checkbox"/> |
| Extension hose 5 m                                 | 4  | 4.440-939.0 |             |             |          |       | 5m extension hose for FRV 30. Connection sleeve included.                                                                                                                                                                                                                                                                                                                                                               | <input type="checkbox"/> |
| Hose fastening attachment kit                      | 5  | 2.642-528.0 |             |             |          |       | Suction cup for fixing the suction hose to smooth surfaces.                                                                                                                                                                                                                                                                                                                                                             | <input type="checkbox"/> |
| Dirt trap attachment kit                           | 6  | 2.642-532.0 |             |             |          |       | Galvanised steel bucket for collecting coarse dirt and for fixing the suction hose in outside areas.                                                                                                                                                                                                                                                                                                                    | <input type="checkbox"/> |
| <b>Hard surface cleaner FR 30</b>                  |    |             |             |             |          |       |                                                                                                                                                                                                                                                                                                                                                                                                                         |                          |
| Surface Cleaner FR 30                              | 7  | 2.642-997.0 |             |             | 300 mm   |       | Up to 10 times greater area coverage compared with the conventional high pressure jet. Plastic casing for optimal manoeuvrability, double ceramic bearing for long working times, flexible connection joint for ergonomic handling and integrated parking position. Machine specific nozzle kit must be ordered separately.                                                                                             | <input type="checkbox"/> |
| <b>FR 30 Me surface cleaner</b>                    |    |             |             |             |          |       |                                                                                                                                                                                                                                                                                                                                                                                                                         |                          |
| Hard surface cleaner FR 30 Me                      | 8  | 2.640-355.0 |             |             | 300 mm   |       | Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry.                                                                                                                                                                                                                                | <input type="checkbox"/> |
| <b>Hard Surface Cleaner FR 50</b>                  |    |             |             |             |          |       |                                                                                                                                                                                                                                                                                                                                                                                                                         |                          |
| Hard surface cleaner FR 50                         | 9  | 2.640-679.0 |             |             | 500 mm   |       | Hot water resistant stainless steel surface cleaner with 500 mm working width. Ideal for large areas. With double ceramic bearings, push handle, non-marking swivel castors and detergent dosing system.                                                                                                                                                                                                                | <input type="checkbox"/> |
| <b>Machine-specific nozzle kits for FR</b>         |    |             |             |             |          |       |                                                                                                                                                                                                                                                                                                                                                                                                                         |                          |
| Nozzle kit for surface cleaners                    | 10 | 2.640-401.0 | 500-650 l/h |             |          |       | Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (500 to 650 l/h).                                                                                                                                                                                                                                                                                                                            | <input type="checkbox"/> |
| <b>Machine-specific nozzle kits for FRV</b>        |    |             |             |             |          |       |                                                                                                                                                                                                                                                                                                                                                                                                                         |                          |
| Nozzle kit 040 - for FRV                           | 11 | 2.642-431.0 |             | 40          |          |       | Machine-specific nozzle kit Kärcher power nozzles and jet nozzle for FRV 30.                                                                                                                                                                                                                                                                                                                                            | <input type="checkbox"/> |
| <b>Machine-specific nozzle kits for FR Classic</b> |    |             |             |             |          |       |                                                                                                                                                                                                                                                                                                                                                                                                                         |                          |
| Nozzle kit for FR Classic 040                      | 12 | 2.885-312.0 |             | 40          |          |       | Nozzle kit specifically for FR Classic surface cleaner.                                                                                                                                                                                                                                                                                                                                                                 | <input type="checkbox"/> |
| <b>FRV 30 Me surface cleaner</b>                   |    |             |             |             |          |       |                                                                                                                                                                                                                                                                                                                                                                                                                         |                          |
| FRV 30 Me                                          | 13 | 2.642-911.0 |             |             |          |       | Thanks to automatic suction of the dirty water, the stainless steel FRV 30 Me Surface Cleaner makes surface cleaning more efficient in both inside and outside areas. Hot water cleaning up to 85°C.                                                                                                                                                                                                                    | <input type="checkbox"/> |
| Extension hose FRV 30 Me and FRV 50 Me             | 14 | 4.441-040.0 |             |             |          |       | 5 m extension hose for FRV 30 Me. Includes connecting adapter.                                                                                                                                                                                                                                                                                                                                                          | <input type="checkbox"/> |

■ Included in the scope of supply. □ Available accessories. ▲ Extension hose.

# HD 6/15-4 CLASSIC

## 1.367-306.0




|                                 |    | Order no.   | Flow rate | Nozzle size | Diameter | Price | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                          |
|---------------------------------|----|-------------|-----------|-------------|----------|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|
| <b>Surface Cleaner FR 50 Me</b> |    |             |           |             |          |       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                          |
| FRV 50 ME                       | 15 | 2.643-598.0 |           |             |          |       | Thanks to automatic suction of the waste water, the stainless steel FRV 50 Me surface cleaner makes surface cleaning more efficient in both inside and outside areas. Hot water cleaning up to 85 °C. The FRV 50 Me features a temperature-resistant 7.5 m polyurethane suction hose. Additional quality features are the non-marking steering rollers and double ceramic bearing. Machine-specific nozzle kit must be ordered separately. Max. 250 bar / 1,300 l/h / 85 °C. | <input type="checkbox"/> |

■ Included in the scope of supply.  
 □ Available accessories.  
 ▲ Extension hose.

# HD 6/15-4 CLASSIC

## 1.367-306.0

**KÄRCHER**



|                                                          |   | Order no.   | Flow rate   |  |  |  | Price | Description                                                                                                                                                                                                                            |                          |
|----------------------------------------------------------|---|-------------|-------------|--|--|--|-------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|
| <b>Cup foam lance</b>                                    |   |             |             |  |  |  |       |                                                                                                                                                                                                                                        |                          |
| Cup foam lance Advanced 042                              | 1 | 6.394-969.0 |             |  |  |  |       | Short, handy foam lance with adjustable spray angle with 1 litre detergent tank. Ideal for cleaning cars due to its compact design.                                                                                                    | <input type="checkbox"/> |
| 1-litre cleaning agent container for advanced foam lance | 2 | 6.414-050.0 |             |  |  |  |       | Additional 1-litre cleaning agent container for quick replacement of the cleaning agent (for foam lance 2.112-017.0 and 2.112-018.0).                                                                                                  | <input type="checkbox"/> |
| <b>Inno Foam Kit</b>                                     |   |             |             |  |  |  |       |                                                                                                                                                                                                                                        |                          |
| Inno Foam Set with detergent injector                    | 3 | 2.640-151.0 |             |  |  |  |       | High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For use with mobile and stationary high-pressure and HDS pressure cleaners for cleaning or disinfection.                                  | <input type="checkbox"/> |
| <b>Easy Foam Set</b>                                     |   |             |             |  |  |  |       |                                                                                                                                                                                                                                        |                          |
| Easy Foam Set with RM injector                           | 4 | 2.640-691.0 |             |  |  |  |       | HP foam system for use with HD/HDS units for cleaning and disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately. | <input type="checkbox"/> |
| <b>Nozzle kits for Inno/Easy Foam Set</b>                |   |             |             |  |  |  |       |                                                                                                                                                                                                                                        |                          |
| Nozzle kit 060 for Inno / Easy Set 600-700 l/h           | 5 | 2.640-687.0 | 600-700 l/h |  |  |  |       | Optimal adaptation to different machine outputs for economic use.                                                                                                                                                                      | <input type="checkbox"/> |
| <b>Foam nozzle mounting kit</b>                          |   |             |             |  |  |  |       |                                                                                                                                                                                                                                        |                          |
| Foam nozzle attachment kit                               | 6 | 2.637-926.0 |             |  |  |  |       | Foaming agent kit. The foam nozzle is ideal for use in sanitary areas and the food industry and wherever long application times are necessary.                                                                                         | <input type="checkbox"/> |

■ Included in the scope of supply. □ Available accessories. ▲ Extension hose.

# HD 6/15-4 CLASSIC

## 1.367-306.0

**KÄRCHER**


|                                                                     |    | Order no.   |  |  |  |  |  | Price | Description                                                                                                                                                                                  |                          |
|---------------------------------------------------------------------|----|-------------|--|--|--|--|--|-------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|
| Cleaning agent injector                                             |    |             |  |  |  |  |  |       |                                                                                                                                                                                              |                          |
| Cleaning agent injector for high pressure (without nozzle)          | 1  | 3.637-170.0 |  |  |  |  |  |       | Cleaning agent dosage at high pressure 3 - 5 %                                                                                                                                               | <input type="checkbox"/> |
| Cleaning agent injector for high and low pressure (without nozzles) | 2  | 3.637-001.0 |  |  |  |  |  |       | Detergent injector for independent high and low pressure dosage. Maximum dosage about 15%.                                                                                                   | <input type="checkbox"/> |
| Machine-specific nozzle kit with order no. 4.637-033.0              |    |             |  |  |  |  |  |       |                                                                                                                                                                                              |                          |
| Nozzle kit HD 500-700 l/h                                           | 3  | 4.769-005.0 |  |  |  |  |  |       | For HD 500 - 700 l/h. Consists of nozzle insert + HP power nozzle + union                                                                                                                    | <input type="checkbox"/> |
|                                                                     | 4  | 4.769-045.0 |  |  |  |  |  |       |                                                                                                                                                                                              | <input type="checkbox"/> |
| Nozzle insert with order no. 4.637-032.0                            |    |             |  |  |  |  |  |       |                                                                                                                                                                                              |                          |
| Nozzle insert up to 1,100 l/h - high pressure                       | 5  | 4.769-003.0 |  |  |  |  |  |       | Nozzle insert for detergent injector 3.637-001 for high-pressure detergent application. For high-pressure cleaners with a water flow rate up to 1100 l/h.                                    | <input type="checkbox"/> |
| Nozzle insert up to 1,100 l/h - low pressure                        | 6  | 4.769-001.0 |  |  |  |  |  |       | For low pressure with machines up to 1.100 l/h                                                                                                                                               | <input type="checkbox"/> |
| Rotary coupling                                                     |    |             |  |  |  |  |  |       |                                                                                                                                                                                              |                          |
| Rotary coupling                                                     | 7  | 4.401-091.0 |  |  |  |  |  |       | Reliably prevents twisting of HP hoses. Connection M 22 x 1.5 m. Handle protection                                                                                                           | <input type="checkbox"/> |
| Coupling                                                            |    |             |  |  |  |  |  |       |                                                                                                                                                                                              |                          |
| Coupler -2 x M22 x 1,5                                              | 8  | 4.403-002.0 |  |  |  |  |  |       | For overriding the dismantled heating coil for cleaning alternative:4.111-029.0 adapter 1 - hose old / hose new                                                                              | <input type="checkbox"/> |
| Connector                                                           |    |             |  |  |  |  |  |       |                                                                                                                                                                                              |                          |
| Nozzle screws / screw socket                                        | 9  | 4.402-022.0 |  |  |  |  |  |       | Nozzle connector/screw connector for connecting high-pressure nozzles and accessories to the high-pressure trigger gun (with nozzle connector). Connectors: 1x M 22 x 1.5 and 1x M 18 x 1.5. | <input type="checkbox"/> |
| Y distributor                                                       | 10 | 4.405-048.0 |  |  |  |  |  |       | Offers the option to connect two spray units to the machine. Installation on the high pressure outlet.                                                                                       | <input type="checkbox"/> |
|                                                                     | 11 | 4.111-024.0 |  |  |  |  |  |       |                                                                                                                                                                                              | <input type="checkbox"/> |
| Adapters                                                            |    |             |  |  |  |  |  |       |                                                                                                                                                                                              |                          |
| Sealing cone complete                                               | 12 | 4.424-004.0 |  |  |  |  |  |       | In order to install high-pressure hose with male coupling on thread with M22 x 1.5 Alternative:4.111-032.0 Adapter 4 - Device new / Hose old Swivel                                          | <input type="checkbox"/> |
| EASY!Lock adapter                                                   |    |             |  |  |  |  |  |       |                                                                                                                                                                                              |                          |
| Adapter 1 M22AG-TR22AG                                              | 13 | 4.111-029.0 |  |  |  |  |  |       | Adapter 1 to connect the old hose with the new hose                                                                                                                                          | <input type="checkbox"/> |
| Adapter 2 M22IG-TR22AG                                              | 14 | 4.111-030.0 |  |  |  |  |  |       | Adapter 2 to connect the old device with the new hose and the old gun with the new hose                                                                                                      | <input type="checkbox"/> |
| Adapter 3 M22IG-TR22AG                                              | 15 | 4.111-031.0 |  |  |  |  |  |       | Adapter 3 to connect the old gun with the new spray lance and new servo regulator                                                                                                            | <input type="checkbox"/> |
| Adapter 5 TR22IG-M22AG                                              | 16 | 4.111-033.0 |  |  |  |  |  |       | Adapter 5 to connect the new gun with the old spray lance and new servo regulator with the old spray lance                                                                                   | <input type="checkbox"/> |
| Adapter 6 TR22IG-M22AG                                              | 17 | 4.111-034.0 |  |  |  |  |  |       | Adapter 6 to connect the new device with the old hose and the old hose with the new gun                                                                                                      | <input type="checkbox"/> |
| Adapter 7 M18IG-TR20AG                                              | 18 | 4.111-035.0 |  |  |  |  |  |       | Adapter 7 to connect the old spray lance with the new nozzle                                                                                                                                 | <input type="checkbox"/> |
| Adapter 8 TR20IG-M18AG                                              | 19 | 4.111-036.0 |  |  |  |  |  |       | Adapter 8 to connect the new spray lance with the old nozzle                                                                                                                                 | <input type="checkbox"/> |
| Adapter 12 rotary coupling EASY!Lock 22 IG - M22 x 1.8 AG           | 20 | 4.111-046.0 |  |  |  |  |  |       | Rotatable adapter for connecting EASY!Force high-pressure gun and high-pressure hoses with M 22x1.5 connection                                                                               | <input type="checkbox"/> |

■ Included in the scope of supply. □ Available accessories. ▲ Extension hose.

# HD 6/15-4 CLASSIC

## 1.367-306.0

**KÄRCHER**



|                                                              |    | Order no.   | Length |  |  |  |  | Price | Description                                                                                                                                                                                                                           |                          |
|--------------------------------------------------------------|----|-------------|--------|--|--|--|--|-------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|
| <b>Automatic, self-winding hose reels for wall mounting</b>  |    |             |        |  |  |  |  |       |                                                                                                                                                                                                                                       |                          |
| Automatic stainless steel hose reel                          | 1  | 6.392-442.0 | 40 m   |  |  |  |  |       | Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses. Compatible high-pressure hose, e.g. order no. 6.110-076.0 (ID 8, 40 m, 400 bar, 1x hose reel connection attachment kit). | <input type="checkbox"/> |
| Powder-coated swivel holder                                  | 2  | 2.639-931.0 |        |  |  |  |  |       | Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose. Rotatable 120°. Galvanised steel.                                                                               | <input type="checkbox"/> |
| Stainless steel swivel holder                                | 3  | 2.641-867.0 |        |  |  |  |  |       | Swivelling wall bracket made of high-grade steel (for 2.641-866). This makes maximum flexibility and convenience possible when working with the HP hose.                                                                              | <input type="checkbox"/> |
| Wall-mounted hose reel                                       | 4  | 2.639-257.0 | 15 m   |  |  |  |  |       |                                                                                                                                                                                                                                       | <input type="checkbox"/> |
| Automatic hose reel, powder-coated steel / plastic           | 5  | 6.392-074.0 | 20 m   |  |  |  |  |       | Automatic hose reel for 20 m high-pressure hose. The console is made from powder-coated steel, the drum is made from plastic.                                                                                                         | <input type="checkbox"/> |
| Automatic stainless steel / synthetic material hose drum     | 6  | 6.392-083.0 | 20 m   |  |  |  |  |       | Automatic hose reel for 20 m high-pressure hose. The console consists of stainless steel, the drum is made from plastic.                                                                                                              | <input type="checkbox"/> |
| Automatic hose reel, coated                                  | 7  | 6.392-106.0 | 20 m   |  |  |  |  |       | Automatic hose reel of durable plastic. Painted steel bracket. Suitable for 20 m high-pressure hose.                                                                                                                                  | <input type="checkbox"/> |
| Hose reel, automatic, basalt grey-coated                     | 8  | 6.392-105.0 | 20 m   |  |  |  |  |       | Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses. For example: order no. 6.110-011.0 (ID 8, 20 m, 315 bar) or order no. 6.110-028.0 (ID 8, 20 m, 400 bar Longlife).        | <input type="checkbox"/> |
| Automatic hose reel, stainless steel, includes swivel holder | 9  | 6.392-076.0 | 20 m   |  |  |  |  |       | Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose.                                                                                                                                        | <input type="checkbox"/> |
| Automatic stainless steel hose reel                          | 10 | 6.392-122.0 | 20 m   |  |  |  |  |       | High-grade, automatic steel hose reel. Especially suitable for use in the food industry. The material and finish provide for a corrosion-resistant, watertight capsuled sprong drive. Connection for HP hoses with nipple.            | <input type="checkbox"/> |

■ Included in the scope of supply. □ Available accessories. ▲ Extension hose.

# HD 6/15-4 CLASSIC

## 1.367-306.0



|                                                                     |   | Order no.   | Nozzle size |  |  |  | Price | Description                                                                                                                                                                                      |                          |
|---------------------------------------------------------------------|---|-------------|-------------|--|--|--|-------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|
| <b>Wet blasting attachment (without nozzle)</b>                     |   |             |             |  |  |  |       |                                                                                                                                                                                                  |                          |
| Wet blasting attachment with flow control (without nozzles)         | 1 | 4.762-010.0 |             |  |  |  |       | Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet.                                                | <input type="checkbox"/> |
| Wet blasting attachment without flow control (nozzles not included) | 2 | 4.762-022.0 |             |  |  |  |       | Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet. Without flow control.                          | <input type="checkbox"/> |
| <b>Nozzle kits for wet jet unit</b>                                 |   |             |             |  |  |  |       |                                                                                                                                                                                                  |                          |
| Nozzle kit for wet jet unit 040                                     | 3 | 2.637-900.0 | 40          |  |  |  |       | Nozzle kit with wet blasting nozzle and nozzle insert (type specific). For optimal Kärcher wet blasting attachment performance. Only in combination with wet blasting attachment 4.762-010/-022. | <input type="checkbox"/> |
| <b>Boron carbide nozzle</b>                                         |   |             |             |  |  |  |       |                                                                                                                                                                                                  |                          |
| Boron carbide nozzle, for machines up to 1,000 l/h                  | 4 | 6.415-084.0 | 6 mm        |  |  |  |       | In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation.                                                                                  | <input type="checkbox"/> |

■ Included in the scope of supply. □ Available accessories. ▲ Extension hose.

# HD 6/15-4 CLASSIC

## 1.367-306.0



|                                          |   | Order no.   |  |  | Price | Description                                                                                                                                                        |                          |
|------------------------------------------|---|-------------|--|--|-------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|
| <b>Geka coupling</b>                     |   |             |  |  |       |                                                                                                                                                                    |                          |
| Geka connector with hose barb, R 3/4"    | 1 | 6.388-455.0 |  |  |       | with hose liner                                                                                                                                                    | <input type="checkbox"/> |
| Geka connector with inner thread, R 3/4" | 2 | 6.388-473.0 |  |  |       | with female thread                                                                                                                                                 | <input type="checkbox"/> |
| <b>Suction filter</b>                    |   |             |  |  |       |                                                                                                                                                                    |                          |
| Water suction filter                     | 3 | 6.414-956.0 |  |  |       | Suitable for ponds, storage tanks or similar, polyamide filter casing, stainless steel strainer, 800 µm mesh, R 3/4" and R 1" connection, without non-return valve | <input type="checkbox"/> |
| Suction filter with check valve          | 4 | 4.730-012.0 |  |  |       | Brass suction filter suitable for ponds, storage tanks, etc. With check valve.                                                                                     | <input type="checkbox"/> |
| <b>Water fine filter</b>                 |   |             |  |  |       |                                                                                                                                                                    |                          |
| Water fine filter, with adapter          | 5 | 4.730-102.0 |  |  |       | Fine-mesh water filter, 125 µm, max. temperature 50°C. Protects the                                                                                                | <input type="checkbox"/> |

■ Included in the scope of supply. □ Available accessories. ▲ Extension hose.

# HD 6/15-4 CLASSIC

## 1.367-306.0



|                             |   | Order no.   |  |  | Price | Description                                                                    |                          |
|-----------------------------|---|-------------|--|--|-------|--------------------------------------------------------------------------------|--------------------------|
| <b>Water supply hose</b>    |   |             |  |  |       |                                                                                |                          |
| Water supply hose           | 6 | 4.440-038.0 |  |  |       | NW 13 R1" / R 3/4", up to 30 °C                                                | <input type="checkbox"/> |
| <b>Backflow check valve</b> |   |             |  |  |       |                                                                                |                          |
| Backflow preventer          | 7 | 2.641-374.0 |  |  |       | To prevent detergent getting into the drinking water cycle in case of inlet at | <input type="checkbox"/> |
| <b>Other HP Accessories</b> |   |             |  |  |       |                                                                                |                          |
| Starting current limiter    | 8 | 2.637-495.0 |  |  |       | Reduces starting current in single-phase supply and protects line fuse.        | <input type="checkbox"/> |

■ Included in the scope of supply.    □ Available accessories.    ▲ Extension hose.

# HD 6/15-4 CLASSIC

## 1.367-306.0



|                                                              |   | Order no.   | Flow rate   |  |  |  | Price | Description                                                                                                                                                    |                          |
|--------------------------------------------------------------|---|-------------|-------------|--|--|--|-------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|
| <b>Push-on washing brush</b>                                 |   |             |             |  |  |  |       |                                                                                                                                                                |                          |
| Push-on wash brush                                           | 1 | 4.762-497.0 |             |  |  |  |       | The wash brush is fitted directly onto the devices' new dual and triple nozzles using clamping.                                                                | <input type="checkbox"/> |
| <b>Rotating washing brush</b>                                |   |             |             |  |  |  |       |                                                                                                                                                                |                          |
| Rotating wash brush for < 800 l/h machines, nylon bristles   | 2 | 4.762-561.0 | 500-800 l/h |  |  |  |       | The rotating wash brush gently removes fine dust and traffic film from all surfaces. Temperature resistant up to 60°C. (M 18 x 1.5, replaceable brush insert). | <input type="checkbox"/> |
| Rotating wash brush for < 800 l/h machines, natural bristles | 3 | 4.762-560.0 | 500-800 l/h |  |  |  |       | Driven by water stream. Gently removes fine dust and traffic film from any surface. Temperature resistant up to 60°C, M 18 x 1.5 (replaceable brush insert).   | <input type="checkbox"/> |

■ Included in the scope of supply. □ Available accessories. ▲ Extension hose.